



## AUBURN LACE PRODUCT MATRIX

Product Name	Function	Performance	Fashion
<b>All Weather Cougar™</b>	Work Boots Speciality Boots, i.e. motorcyclist, fire jumper, etc	Fire Resistant: NFP 1977 Certified Non Wicking: Gore Approved Std Thickness: 3.5mm, +/- 0.4mm Pull Strength: 90 lbs (3.6mm x 3.5mm) Knot Slippage: TBD	Surface: Oily to touch Flesh: Oiled down Colors: Tan, Brown, Black, Burgundy
<b>Genuine Rawhide Classic™</b>	Boat Shoes (M's & W's) Upper Material: Full Grain Leather	Std Thickness: 3.0mm, +/- 0.2mm Pull Strength: 55 lbs (3.2mm x 2.8mm) Crocking Resistance: ASTM D5053 - 3.0 (also SATRA) Colorfastness to H2O: none Knot Slippage: TBD	Surface: Tacky, "Cheesy" to touch Flesh: Natural Colors: Refer to Color Palette *Best overall "tie-ability"
<b>Classic Plus™</b>	Deck Shoes Moccasins Dress Shoes / Boots (W) Upper Materials: Suede Synthetic, i.e. Canvas	Std Thickness: 2.6mm, +/- 0.2mm Pull Strength: 55 lbs (3.2mm x 2.8mm) Crocking Resistance: ASTM D5053 - 3.5 (also SATRA) Colorfastness to H2O: AATCC 107 - 3.5 (also SATRA) Knot Slippage: TBD	Surface: No residual / Slick to touch Flesh: "Leather Dust Free" Colors: Refer to Color Palette
<b>Casual</b>	<b>Economical</b> styles of: Boat/Deck Shoes Slippers Moccassins	Std Thickness: 2.2mm, +/- 0.2mm Pull Strength: 35 lbs (3.6mm x 2.4mm) Crocking Resistance: none Colorfastness to H2O: none Knot Slippage: TBD	Surface: No residual / Slick to touch Flesh: No residual / Slick to touch Colors: Refer to casual lace price list (10 colors available)
<b>Decorative</b>	Handsewns: Collar, Kicker Indoor Slippers: Bow Tie  *Available only up to 36"	Std Thickness: 2.4mm, +/- 0.4mm Pull Strength: 25 lbs (3.2mm x 2.4mm) Crocking Resistance: ASTM D5053 - 3.0 (also SATRA) Colorfastness to H2O: none	Surface: Tacky, "Cheesy" to touch Flesh: Natural Colors: Subject to Demand *Available only up to 36"

Revised 11/13/14 - Int'l version

Auburn Leather Company  
125 Caldwell St.  
Auburn, KY 42206  
800.635.0617  
www.auburnleather.com